

VPL-FH31

4,300 lumens WUXGA 3LCD Installation projector



Overview

High brightness and low maintenance - great performance for any environment

The VPL-FH31 is designed to fit smoothly into almost any environment where a high-quality projector is required. Its brightness, zoom and throw range, coupled with its wide lens shift range, mean it can perform where other projectors would struggle - even in high ambient light.

Once installed, the VPL-FH31 has excellent image capabilities and a long lifespan that delivers low Total Cost of Ownership. Sony's BrightEra technology improves and maintains colour purity throughout the life of the system by protecting the LCD panels against harmful ultra violet light. Clever features such as synchronised lamp and filter replacement cycles reduce costs and downtime.

Featuring the usual wide range of features, the VPL-FH31 also allows for edge blend (multiple projectors with seamless connection), warping and Portrait mode installation for retail, corporate signage applications. Other features include advanced projection capabilities such as side-by-side image projection and DICOM medical training, the VPL-FH31 is an obvious projector choice for venues that demand quality, unique installation locations and practicality.

Features

- **3 LCD WUXGA BrightEra Panel Technology**

Sony's BrightEra Panel Technology gives more accurate colour rendition, higher brightness and longer lifespan for a lower Total Cost of Ownership.

- **Ultra High Resolution**

The VPL-FH31's WUXGA (1920x1200) 16:10 format resolution delivers absolute best image quality.

- **Very High Brightness: 4,300 Lumens Colour Light Output**

With very high brightness of 4,300 Lumens Colour Light Output, the VPL-FH31 gives a clearer image in high ambient light, making it highly suitable for larger venues.

- **Wide Zoom Range (x1.6) and Throw Ratio (1.4 to 2.3) as standard**

The standard lens has a wide zoom capability and throw ratio, offering more flexibility over the positioning of the projector, which can be installed closer to or further away from the screen

- **Wide Lens Shift Range: Vertical: +60%, Horizontal: +/- 32%**

The VPL-FH31's wide lens shift range means that the projector can be positioned closer to the ceiling, or horizontally offset to avoid ceiling obstacles.

- **Long Lamp Replacement Time: 3,000-4,000 hours (High/Std)**

Longer lamp life means fewer visits by maintenance personnel and lower Total Cost of Ownership.

- **Lamp/Filter Replacement Cycles Synchronised**

Synchronised lamp and filter replacement effectively halves the number of visits needed to maintain the projector in peak operating condition.

- **Interchangeable Lenses: Z1024, Z1032**

The VPL-FH31 allows you to choose different lenses for increased flexibility.

- **Edge Blend**

Multiple VPL-FH31 projectors have the ability to project a single seamless image onto a screen (wall) creating an exciting visual event, or retail or corporate signage application.

- **Warping Projection**

Warping projection allows the customer to adjust the corners and sides of a VPL-FH31 projected image to any convex or concave screen set up or wall for dynamic signage displays.

- **Portrait Mode**

The VPL-FH31 can be installed on its side (fan side down) for any portrait signage application.

- **Side by Side Image Projection**

Side by side twin image gives you the ability to project from two inputs (RGB + any other Input) at the same time, making the projector ideal for applications like video conferencing and DICOM medical training.

- **DICOM GSDF Simulation**

The VPL-FH31 offers DICOM GSDF Simulation (HDMI with computer signals), which conforms to GSDF (Grayscale Standard Display Function) of medical standards for DICOM (Digital Imaging and

Communication in Medicine).

- **Wide Range of Image Adjustments**

This wide range of image adjustments allows the projector to be installed in almost any location. Where equipment is being upgraded, installers are more likely to be able to use existing mounts. In new installations, they are more likely to be able to work around existing obstructions.

- **User Panel Alignment**

Pixel alignment shifts the entire image or desired range (H: 16 X V: 10 pixels) for complete colour correction.

- **Colour Matching**

The VPL-FH31 offers brightness and colour matching adjustment to the original image for complete image accuracy.

- **Lower Operating Power Consumption than Previous Models**

Lower operating power consumption helps reduce energy consumption and lowers running costs.

Technical Specifications

Display system	
● Display system	3 LCD system

Display device	
● Size of effective display area	0.76" (19.3 mm) x 3 BrightEra LCD Panel, Aspect ratio: 16:10
● Number of pixels	6,912,000 (1920 x 1200 x 3) pixels

Projection lens*1	
● Focus	Manual
● Zoom - Powered/Manual	Manual
● Zoom - Ratio	Approx. x 1.6
● Throw ratio	1.39:1 to 2.23:1
● Lens shift - Powered/Manual	Manual
● Lens shift - Range Vertical	+60%
● Lens shift - Range Horizontal	+/- 32%

Light source	
● Type	Ultra high pressure mercury lamp
● Wattage	330 W type

Recommended lamp replacement time*2	
● Lamp mode: High	3000 H
● Lamp mode: Standard	4000 H

Filter cleaning / replacement cycle*2 (Max.)*2	
● Filter cleaning / replacement cycle*2 (Max.)	15000 H (Cleaning) Same as the lamp replacement is recommended

Screen size*1	
● Screen size	40" to 600" (1.02 m to 15.24 m) (measured diagonally)

Light output	
● Lamp mode: High	4300 lm
● Lamp mode: Standard	3400 lm

Color light output	
● Lamp mode: High	4300 lm
● Lamp mode: Standard	3400 lm

Contrast ratio (full white / full black)*3	
● Contrast ratio (full white / full black)*3	2000:1

Displayable scanning frequency	

● Horizontal	14 kHz to 93 kHz
● Vertical	47 Hz to 93 Hz

Display resolution	
● Computer signal input	Maximum display resolution: 1920 x 1200 dots *4
● Video signal input	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p, 1080/24p

Color system	
● Color system	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60

Keystone correction (Max.)*8	
● Vertical	+/- 30 degrees
● Horizontal	+/- 30 degrees

OSD language	
● OSD language	23-languages (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Polish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Vietnamese, Arabic, Farsi, Indonesian, Finnish, Hungarian)

INPUT OUTPUT (Computer/Video/Control)	
● INPUT A	RGB / YPbPr input connector: 5BNC (female) Audio input connector: Stereo mini jack
● INPUT B	RGB input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack (shared with INPUT C)
● INPUT C	DVI-D input connector: DVI-D 24-pin (Single link), HDCP support Audio input connector: Stereo mini jack (shared with INPUT B)
● INPUT D	HDMI input connector: HDMI 19-pin, HDCP support
● S VIDEO IN	S video input connector: Mini DIN 4-pin Audio input connector: Pin jack (x2) (shared with VIDEO IN)
● VIDEO IN	Video input connector: Pin jack Audio input connector: Pin jack (x2) (shared with S VIDEO IN)
● OUTPUT	Monitor output connector*5: Mini D-sub 15-pin (female) Audio output connector*6: Stereo mini jack (variable out)
● REMOTE	RS-232C connector: D-sub 9-pin (female)
● LAN	RJ-45, 10BASE-T/100BASE-TX
● IR (Control S)	Control S input connector: Stereo mini jack

Acoustic noise	
● Lamp mode: Standard	30 dB

Operating temperature / Operating humidity	
● Operating temperature / Operating humidity	0°C to 40°C (32°F to 104°F) / 35% to 85% (no condensation)

Storage temperature / Storage humidity	
● Storage temperature / Storage humidity	-20°C to +60°C (-4°F to +140°F) / 10% to 90% (no condensation)

Power requirements	
● Power requirements	AC 100 V to 240 V, 4.0 A to 1.6 A, 50/60 Hz

Power consumption	
● AC 100 V to 120 V	Lamp mode: High: 400 W

● AC 100 V to 120 V	Lamp mode: High: 380 W
Power Consumption (Standby Mode)	
● AC 100 V to 120 V	0.2 W (when "Standby mode" is set to "Low")
● AC 220 V to 240 V	0.3 W (when "Standby mode" is set to "Low")
Power Consumption (Networked Standby Mode)	
● AC 100 V to 120 V	9.2 W (LAN) (when "Standby Mode" is set to "Standard")
● AC 220 V to 240 V	10.4 W (LAN) (when "Standby Mode" is set to "Standard")
Standby Mode / Networked Standby Mode Activated	
● Standby Mode / Networked Standby Mode Activated	After about 10 Minutes
Heat dissipation	
● AC 100 V to 120 V	1365 BTU/h
● AC 220 V to 240 V	1297 BTU/h
Dimensions (W x H x D)	
● Dimensions (W x H x D) (without protrusions)	Approx. 390 x 134 x 463 mm (15 11/32 x 5 9/32 x 18 7/32 inches)
Mass	
● Mass	Approx. 8.3 kg (18 lb)
Supplied accessories	
● Remote commander	RM-PJ19
Optional accessories	
● Replacement lamp	LMP-F272
● Projection lenses	VPLL-Z2009/Z1024/Z1032/2007
● Projection lens adapter	PK-F30LA1
Notes	
● *1	With supplied standard lens
● *2	This figure is expected maintenance time, not guaranteed time. The actual value depends on the environment and how the projector is used.
● *3	The value is average.
● *4	Available for VESA Reduced Blanking signal.
● *5	From INPUT A and INPUT B.
● *6	Works as an audio switcher function. Output from a selected channel; not available in standby.

Accessories

Ceiling Brackets



PSS-610
Projector Ceiling Bracket for the VPL-F Series



PSS-650
Projector Ceiling Bracket for Installation



PSS-650P
Projector Ceiling Bracket for Installation

Lamps



LMP-F272
Replacement Lamp for the VPL-F Series

Lenses



VPLL-2007
Projection Lens for the VPL-F Series



VPLL-Z1024
Projection Lens for the VPL-F Series



VPLL-Z1032
Projection Lens for the VPL-F Series



VPLL-Z2009
Projection Lens for the VPL-F Series

Other Accessories



PK-F30LA1
Lens adaptor