Multimedia Projector







Bright and Light

You can enjoy beautiful and clear images whenever you go without worrying about ambient light levels



Up to Three Times Brighter Colors

3LCD projectors produce up to three times brighter colors compared to 1-chip projectors





Flexible Installation

There are a variety of installation choices* — ceiling mount, floor mount or light track mount for ease and flexibility *Optional mount kit is required



Built-in Edge Blending

For bigger, more dynamic displays, the edge blending function allows you to seamlessly join several projections together



WUXGA Resolution

Images can be projected on a large screen with no information left out



Longer Lamp and Filter Life — 10,000 Hours

The long 10000H lamp and filter life saves time and money by reducing the frequency of costly lamp and filter replacement



Image Shift

You can adjust the projected position easily when using digital zoom functionality



Epson Projector Content Manager

The Epson Content Manager gives you a whole range of control, including scheduling and editing playlists



Multimedia Projector EB-U50

SPECIFICATIONS

Main Parts	LCD	Size			0.67-inch
IVIDITI F di LS	LCD	Pixel Number			
		Native Resolution		2,304,000 dots (1920 x 1200) x 3 WUXGA	
					16:10
	Ducie stien Lene	Aspect Ratio			
	Projection Lens	Type	1	Optical Zoom (Manual) / Focus (Manual)	
		F-Number / Focal Lengt	h	1.50-1.71 / 20.42mm-24.50mm	
		Zoom Ratio		1-1.2	
		Throw Ratio		1.38-1.68	
		Screen Size (Projected D	vistance, Zoom: Wide)	30" to 300" [0.87 to 9.02 m]	
		Screen Size (Projected D	istance, Zoom: Tele)	30" to 300" [1.07 to 10.98m]	
		Offset		10:1	
	Lamp	Туре		200W UHE	
		Lamp Life (Normal / ECC))	10000 hours / 17000 hours	
White Light Output					3700 lm (Color mode: Dynamic, Zoom: Wide)
Color Light Output					3700 lm (Color mode: Dynamic, Zoom: Wide)
Contrast	Auto iris : ON (Color mod	e : Dynamic, Power Consum	16000:1		
		(Iris: Open) / Black (Iris: Close)			
Color Reproduction					Up to 1.07 billion colors
Color Processing					10bit
Internal Speaker(s)	Sound Output				5W Monaural
Content Playback	- ouna output				Yes
	Imago	Color Mode			Dynamic
Adjustment Function	Image	COIOI MODE		· ·	
				Presentation	
					Cinema
					sRGB
				Blackboard	
				Multi-Projection	
		Brightness		Yes	
		Contrast		Yes	
		Color Saturation		Yes	
		Tint		Yes	
	Settings	Geometry Correction V Keystone			-30 degrees to +30 degrees
		····, ···	H Keystone		-30 degrees to +30 degrees
			Auto Keystone Corr	ection	Vertical: -30 to +30 degrees
			Quick Corner		Yes
		Schedule Settings	Quick conner		Yes
Video I/O	IN		D-sub 15pin	PCP Component PCP Video	
VILLEO I/O	IIN	Analog		RGB, Component, RGB-Video	
		Digital	HDMI		2
	Out	Analog	D-sub 15pin	RGB, RGB-Video	1
Audio I/O	IN	Stereo mini		2	
	Out	Stereo mini		1	
Control I/O	RS-232C	D-sub 9pin			1
USB-I/O	Type A (for USB Memory,	USB Document Camera, for	1		
	Type B (for USB Display, 0	Control, Firmware update)	1		
Network I/O	Wired LAN	RJ45	1		
	Wireless LAN	Built-in			1
Direct Power On					Yes
Direct Power Off					Yes
Start-up Period					about 6 seconds
					warm-up period: 30 seconds
Cool-down Period					Instant off
Air Filter	Maintonanea Cuela (D	or concumption Named / FC	·())		
	maintenance Cycle (Pow	er consumption: Normal / EC	0)		10000H / 20000H
Power Supply Voltage			100 - 240 V AC +/- 10%, 50/60 Hz		
Power Consumption	220-240V Area	Lamp On (Power consur	285W / 218W		
		Networked Standby / Er	2.0W / 0.3W		
Dimension	Exclude Feet (W x H x D)				364×87×248 mm
					Approx. 6.83 lbs. / 3.1 kg
Weight					Approx. 0.05 lb3.7 5.1 kg

Supplied Accessories

Optional Accessories

Ceiling Mount / Floor Stand

Lighting Track Mount

Spare Lamp

Air Filter Set

Supplied Accessories
Quick Started Quide
Remote Control
Battery for Remote Control (AA x 2)
Interface Cover
Power Cable (1.8m)
PC Cable (1.8m)

ELPLP97

ELPAF59

ELPMB60

ELPMB61

	16:10 Screen Size (Inch)	Projection Distance						
		Wi	ide	Tele				
		cm	inch	cm	inch			
	80	238	94	291	114			
	100	299	118	364	143			
	150	450	177	548	216			
	200	601	236	731	288			



2 Year Onsite Warranty Service to be provided for local purchase only. # The warranty service can be extended by purchasing Epon Coverputs Extended Warranty. For more information, please contact Epson customer support. For Standard warranty terms & condition refer to https://www3.epson.com.hk/eserv

Bold, Bright, Beautiful...3LCD Technology

Opti

3LCD technology achieves bright, natural images and smooth, sharp video playback. No color break-up makes images gentle on the eyes.

HK Sales Hotline HK Technical Hotline





Epson Hong Kong Limited Unit 715-723, 7/F Trade Square, 681 Cheung Sha Wan Road,Cheung Sha Wan, Kowloon, H.K. *Please call our sales hotlines for demonstration at our showroom.

Epson Authorized Customer Service Centre

Wah Fung Computer Services Ltd. Unit 901, 9/F, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong Macau Hotline

: (853) 2850 8065 URL: www.epson.com.hk

AUG19-01-PROJECTOR

: (852) 2827 8711 : (852) 2827 8911