



# **Product Specification**

Product Type: LED All-in-one Display Terminal

Product Model: QM2712 (MWALL Plus)

Version: V1.0

**Product Specification** 









## **Product Features**

- ◆ TOP 2210 LED and GOB for better protection.
- ◆ Foldable transportation, electric lift, easy installation, Easy transportation from elevator to office, plug-and-play operation.
- ◆ All-in-One with slim body and light weight modular design to save your space and make your boardroom brilliant.
- ◆ Initiate three-in-one integrated design of power supply, bridge board and receiving card to reduce electromagnetic interference.
- ◆ Ultra-large viewing angle plus 8 brightness levels, easy to adjust brightness according to the environments.
- Remote control with interfaces adapting USB, HDMI and etc.
- ◆ Integrated with external device, wireless screen transmission via PC, mobile phone and tablet, instant interaction at any moment.





Ratio



16:9

#### **Product Parameter**

#### **Display Parameter**

Size 110 inch
Pixel Pitch 1.2mm

Resolution 1920×1080

Module Size (width\*height) 152.5×343mm

Cabinet Size

610×343×31mm (width\*height\*thickness)

Cabinet Qty 4x4

Overall Dimension

(width\*height)

Display area (width\*height) 2440×1372mm

**Unfolded Terminal Size** 

(width\*height\*thickness)

2453×2318×760mm

Folded Terminal Size

(width\*height\*thickness)

1360×1817×760mm

Terminal Height 1817~2317mm Adjustable

Weight 210kg

Suggested Viewing Distance ≥2m

Maintenance Front & Rear Maintenance

Installation Method Foot mounting

### **System Parameter**

Operating System Android 9.0

CPU 2 x Cortex-A72 + 4 x Cortex-A53, 2.0GHz

RAM 4GB

Storage 32GB







Support MPEG1, MPEG2, MPEG4, H.264, WMV, MKV, TS, FLV and
other mainstream video formats; Support MP3 and other audio
formats; Support JPG, JPEG, BMP, PNG, and GIF image formats

# **Optical Parameter**

Brightness	550nit
Refresh Rate	3840Hz
Gray Scale	14bit
Contrast	6500:1
ССТ	6500-9300K

Viewing Angle Horizontal 170°, Vertical 170°

LED Lifespan ≥100,000h

#### **Electrical Parameter**

Input Voltage	100-240VAC 50/60Hz
Average Consumption	0.44KW
Maximum Consumption	1.31KW

#### **Environmental Parameter**

Ambient Temperature	-10℃-40℃
Humidity	10%~80%RH No condensation

#### Note:

- 1. The content of this specification may be adjusted and revised in real time without prior notice to provide as accurate specification parameters as possible
- 2. This product is an indoor product. It is strictly prohibited to use it in direct sunlight
- 3. In order to ensure long-term and more uniform display effect, do not play fixed images for a long t ime







# Introduction to button and interface



No	Description	
1	Light sensor	
2	IR	
3	Type C port	
4	USB 3.0 port	
5	USB 2.0 port	
6	Menu button (including brightness, color temperature, contrast, sound, signal source, test mode and other sub-menus)	
7	Bright/OK (1. It is a brightness adjustment button when the menu is not brought up, for adjusting the brightness in cooperation with the + and - keys;  2. Confirm button when the menu is brought up)	
8	In the brightness adjustment mode, it is the brightness decrease button; In the brightness adjustment menu, it is the Down/Decrease button	
	In the brightness adjustment mode, it is the brightness increase button;	
9	In the brightness adjustment menu, it is the Up/Increase button	
10	Standby/Wake up button	
11	Two-color indicator light (red/blue)	
12	HDMI input port (toward the bottom)	







13

## 3.5 Audio output port (toward the bottom)

Buttonicon  C) Standby/Wakeup  Up  Down  Confirm  Left  Right  Voice +  Voice -  Back  Brightness Adjustment
Up Down Confirm Left Right Voice + - Voice - Back
Down Confirm  Left Right  Voice +  Voice -  Back
Confirm  Left  Right  Voice +  Voice -  Back
Left Right  Voice +  Voice -  Back
Right  Voice +  Voice -  Back
+ Voice + - Voice Back
Voice - Voice - Back
Voice - Back
Back
,
Brightness Adjustment
E Channel Switch
Main Interface

# Packing Dimension

Tool kit

Front maintenance tool

Remote Control

Item	Dimension	Quantity
Cabinet and Module Packing Dimension	1374*774*1878mm	1

1 Set

1 Set

1 Set







#### Note:

 In case of special requirements, the packing quantity, weight and dimension may change, and the actual product received shall prevail.

#### **Special Statement**

- ◆ Intellectual Property Rights: The hardware design and software programs of this product are protected by copyright. The contents of this product and the manual shall not be copied without the authorization of the company.
- ◆ The contents of this manual are for reference only and do not constitute a commitment of any kind.
- ◆ The company reserves the right to make improvements and changes to the product design without prior notice
- ◆ Note: HDMI, HDMI HD Multimedia Interface and HDMI logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

